

IN THE CLAIMS:

The text of all pending claims, (including withdrawn claims) is set forth below. Cancelled and not entered claims are indicated with claim number and status only. The claims as listed below show added text with underlining and deleted text with ~~striketrough~~. The status of each claim is indicated with one of (original), (currently amended), (cancelled), (withdrawn), (new), (previously presented), or (not entered).

Please CANCEL claims 2, 12, 14, 15, 16, 18, and 19 without prejudice or disclaimer.

Please AMEND claims 1, 13, and 20 in accordance with the following:

1. (CURRENTLY AMENDED) A mobile device communications system which has a plurality of service providing servers, and is used for communications by a mobile terminal, comprising:

a first network unit which is connected to the mobile terminal and has a plurality of input/output points to and from the service providing servers;

a plurality of first communications distribution units respectively connected to the plurality of input/output points;

a second network unit connected to said plurality of first communications distribution ~~units~~unit;

a third network unit connected to the plurality of service providing servers; and

a plurality of second communications distribution units which are connected between said second network unit and said third network unit, for distributing a series of communications between the mobile terminal and any of the plurality of service providing ~~server~~ servers to any of the plurality of service providing ~~server~~ servers, where

said first communications distribution unit distributes ~~said~~ a series of communications between said mobile terminal and any of said plurality of service providing servers to any of said plurality of second communications distribution units through said second network unit, wherein

each of said plurality of first communications distribution units comprises a same storage contents of distribution destination storage unit storing any of said plurality of second communications distribution units to which a series of communications are to be distributed corresponding to an identifier of a session as the series of communications between the mobile terminal and the service providing servers.

2. (CANCELLED)

3. (PREVIOUSLY PRESENTED) The system according to claim 1, wherein:
the plurality of service providing servers form a plurality of groups each being configured by servers providing same services;
the mobile terminal specifies a representative address for each of the plurality of groups to communicate with service providing servers; and
said second communications distribution unit distributes the series of communications to any of the service providing servers in a group specified by the representative address.

4. (PREVIOUSLY PRESENTED) The system according to claim 3, wherein when the mobile terminal changes the representative address for a change of a service to be obtained in the series of communications by the mobile terminal, said second communications distribution unit distributes subsequent communications in the series of communications to any of the service providing servers in the group specified by the representative address after the change to continue the series of communications.

5. (ORIGINAL) The system according to claim 1, further comprising
a service authentication unit checking whether or not a user of the mobile terminal has a right to receive a service provided by the service providing servers when said second communications distribution unit distributes the series of communications to any of the plurality of service providing servers.

6. (PREVIOUSLY PRESENTED) The system according to claim 1, wherein:
said second communications distribution unit can distribute the series of communications not only to the plurality of service providing servers, but also to a server external to said mobile device communications system; and
said system further comprises an accounting information generation unit generating accounting information about a service received by the mobile terminal from the service providing servers or a server external to said mobile device communications system.

7. (ORIGINAL) The system according to claim 1, further comprising
a session management device assigning an identifier to a session as a series of communications between the mobile terminal and the service providing servers to manage the identifier.

8. (PREVIOUSLY PRESENTED) The system according to claim 7, wherein said second communications distribution unit assigns an identifier to a user session as a series of communications in a layer higher than a layer corresponding to a session managed by said session management device in a hierarchical structure of communications, and distributes communications in the user session between the mobile terminal and the service providing servers to any of the plurality of service providing servers.

9. (PREVIOUSLY PRESENTED) The system according to claim 8, wherein there are a plurality of types as types of the user session, and said second communications distribution unit distributes communications in the user session corresponding to the type of the user session.

10. (PREVIOUSLY PRESENTED) A mobile device communications method for use with a plurality of service providing servers for communications by a mobile terminal, comprising:
the mobile terminal transmitting a packet in a series of communications by specifying any of the plurality of service providing servers;

a load balancer, which received the packet, distributing the packet to any of the plurality of packet gateway devices corresponding to an identifier for the series of communications; and

said packet gateway device which was assigned the packet distributing the packet to any of the plurality of service providing servers performing the same services as the service providing server specified by the mobile terminal.

11. (PREVIOUSLY PRESENTED) The method according to claim 10, wherein:
the series of communications are a session managed by a session management device;
and

said packet gateway device distributes a packet corresponding to a user session as a series of communications in a layer higher than a layer corresponding to the session in a hierarchical structure of communications.

12. (CANCELLED)

13. (CURRENTLY AMENDED) The A computer-readable portable storage medium which is used by a computer configuring a packet gateway device for distributing communications to a service providing server between a plurality of load balancers and service

providing servers connected to a network to which a mobile terminal is connected in a mobile device communications system having the plurality of service providing servers for establishment of communications performed by the mobile terminal, and stores a program used to direct the computer to perform operations comprising:

storing a destination address and a source address of a packet received from the load balancer using a unique source port number as a key;

setting the unique source port number as a source port number of a packet header;

selecting any of a plurality of service providing servers capable of providing a service requested by the mobile terminal from among the plurality of service providing servers such that the loads of the service providing servers can be balanced; and

transmitting a packet to the service providing server with an address of the selected service providing server set as a destination address, and an address of the device set as a source address according to claim 12, wherein an identifier for a user session as a series of communications in a layer higher than a layer corresponding to a session as a series of communications between the mobile terminal and the service providing server in a hierarchical structure of communications is used as the unique source port number.

14. - 16. (CANCELLED)

17. (PREVIOUSLY PRESENTED) A computer-readable portable storage medium which is used by a computer configuring a packet gateway device for distributing communications to a service providing server between a plurality of load balancers and service providing servers connected to a network to which a mobile terminal is connected in a mobile device communications system having the plurality of service providing servers for establishment of communications performed by the mobile terminal, and stores a program used to direct the computer to perform operations comprising:

retrieving from a packet received from the load balancer a destination address and a source address of the packet when a series of communications between the mobile terminal and the service providing server start, and setting the addresses in an accounting record;

incrementing a number of packets of an accounting record each time a packet is received from the load balancer until the series of communications terminate, retrieving a packet length from the received packet, and adding the packet length to the packet length of the accounting record; and

setting again the source address of the accounting record into identification information

about a user of the mobile terminal, and the destination address into information about the service providing server.

18. - 19. (CANCELLED)

20. (CURRENTLY AMENDED) A mobile device communications system which has a plurality of service providing servers, and is used for communications by a mobile terminal, comprising:

a network unit which is connected to the mobile terminal and has a plurality of input/output points to and from the service providing servers;

a plurality of first communications distribution units respectively connected to the plurality of input/output points; and

a plurality of second communications distribution units, connected between said plurality of first communications distribution units and the plurality of service providing servers, for distributing a series of communications between the mobile terminal and the service providing server to any of the plurality of service providing servers, where although the communications between the mobile terminal and the service providing server are performed through any of the plurality of input/output points of the network unit from start to termination of the series of communications, any of said plurality of first communications distribution units distributes the series of communications to a same second communications distribution unit from among said plurality of second communications distribution units, corresponding to an identifier of a session as the series of communications between the mobile terminal and the service providing servers.